

**F-WB...B... Annular space sealing**

The ANNULAR SPACE SEALING “FV-WB...B...” Is a pressure tight annular sealing between all Flexalen pipe systems and core drilled holes / scabbard tubes for wall openings.



**Description:**

The 40mm (or 2x 40mm) wide rubber element is compressed by means of two metallic discs. The Flexalen annular space sealing seals the annular space between the Flexalen casing pipe and the core drilled hole or the scabbard tube against water.

**Technical details:**

Pressure plates	V2A (Stainless steel)
Pressure tightness	0.5 bar corrugated casing / 3 bar smooth casing
Rubber thickness	2 x 40mm (40mm for casing pipes OD40,50mm)
Rubber quality	EPDM
Temperature range	-30°C up to +120°C
Shore A	40 +/- 5°
Wall opening min/max	125 – 400mm

**Applicability:**

CODE	Flexalen Casing OD [mm]	Core drilled hole ID [mm]
F-WB040B100	40	100
F-WB050B100	50	100
F-WB063B125	63	125
F-WB075B125	75	125
F-WB090B150	90	150
F-WB125B200	125	200
F-WB160B250	160	250
F-WB200B300	200	300
F-WB225B350	225	350
F-WB250B350	250	350
F-WB315B400	315	400